

WOODMAXX™

Premium Band Saw Blades

- High Precision Ground Teeth
- High Tolerance Balanced Set
- Set of the Art Tooth Hardening

For Thin Kerf Saw Mills and
Horizontal & Vertical Re-Saws

Hook Angle Guide

10°
all-purpose blade & for mixed hardwoods

7°
for extreme hardwoods; frozen, exotic,
seasoned or difficult woods

4°
for extreme hardwoods & frozen woods

Tooth Spacing Guide

1/2" (2 TPI)
Resawing

3/4" (1.3 TPI)
All purpose

7/8" (1.1 TPI)
All purpose

1" (1 TPI)
Higher horsepower, high production

WoodMaxx Profiles and Sizes

Width x Thickness (in.)	Hook Angle					
	10°			7°	4°	
	Teeth Per Inch (TPI)					
	2	1.3	1.1	1	1.1	1.1
1 x .042		•				
1-1/8 x .035	•	•				
1-1/4 x .042		•	•	•	•	•
1-1/4 x .045			•		•	•
1-1/2 x .042			•			
1-1/2 x .050			•		•	•
1-1/2 x .055			•		•	•
2 x .042				•		
2 x .050				•		

PALLETMAXX™

Premium Dismantler Blades

- Aggressive Tooth Design
- Engineered for Dismantling Machines
- Available in Carbon Steel and Bi-Metal

FOLLOW US



Kasco LLC



kasco_llc